

Technical specifications

ETERNAL

This heterogeneous project vinyl meets the requirements of EN 649 and EN 651



		Wood/Form	Wood decibel
Classification	EN 685	34/42	34/42
Collection size		12/40	12
Total thickness	EN 428	2.2 mm	3.4 mm
Thickness wear layer	EN 429	0.7 mm	0.7 mm
Roll width	EN 426	2.00 m	2.00 m
Roll length	EN 426	25 m	25 m
Weight	EN 430	2.85 kg/m ²	3.1 kg/m ²
Static charge	EN 1815	≤ 2 kV	≤ 2 kV
Slip resistance	ZH 1-571	R9	R9
Fire rating	EN 13501-1	B _i s1	B _i s1
Impact sound reduction	EN ISO 717-2	≥ 8 dB	≥ 17 dB
Wear resistance (group)	EN 660-1 (EN 649)	Group T	Group T
Castor chair resistance	EN 425	No effect	No effect
Residual indentation	EN 433	0.06 mm	< 0.15 mm
Colour fastness	ISO 105-B02	6-7	6/7
Thermal conductivity	DIN 52612	0.015m ² K/W	0.015m ² K/W
Chemical resistance	EN 423	Good resistance	Good resistance
Dimension stability	EN 434	< 0,10%	< 0,10%
Reversed installation		No/Yes	No

The above information is subject to modifications for the benefit of further improvements.