

SARLON® traffic

Technical specifications

This heterogeneous project vinyl meets the requirements of EN 651

	Total thickness	EN 428	3.4 mm (3.25 mm*)
	Domestic heavy	EN 685	Class 23
	Commercial heavy	EN 685	Class 33
	Commercial very heavy	EN 685	Class 34
	Industrial general	EN 685	Class 42
	Collection size		60
	Thickness wear layer	EN 429	0.67 mm (0.52 mm*)
	Roll width	EN 426	2.00 m
	Roll length	EN 426	± 25 m
	Total weight	EN 430	2.9 kg/m ² (2.7 kg/m ²)
	Abrasion resistance	EN 660-1	Group T
	Electrical resistance	EN 1081	≥ 10 ⁹ Ω
	Accoustical impact noise reduction	EN ISO 717-2	19 dB
	Castor chair continuous use	EN 425	No damage
	Indentation-residual	EN 433	< 0.16 mm
	Furniture leg test	EN 424	No damage
	Light fastness	ISO 105-B02	7
	Resistance to chemicals	EN 423	Good
	Fungus resistance	EN ISO 846	Rate 0
	Dimension stability	EN 434	< 0.1%

Sarlon traffic meets the requirements of EN 14041



	Reaction to fire	EN 13501-1	C _{flr} s1
	Slip resistance	EN 13893	DS: ≥ 0.30
	Body voltage	EN 1815	≤ 2 kV
	Thermal conductivity	EN 12524	0.25 W/m-K

* Also available

Sarlon traffic hoggar also available in 50 x 50 cm tiles. (17 dB)

The above information is subject to modifications for the benefit of further improvements.